Boca Systems
Solutions for the Ticketing Industry

Lemur-FSP
Flight Strip Printer

General
Print Method: direct thermal
Print Speed: 10" per sec. maximum
Resolution: 203 dpi (8 dots/mm); 300 dpi
600 dpi (premium upgrade)
Size: 7.7 H x 6.5 W x 8.25 L
Weight: 9.5 pounds

Media Transport
Media Type: fanfolded tickets
Ticket Thickness: .004" to .011"
Ticket Width: 1" to 2"
Positioning: optical detector senses
black mark
Ticket Separation: Intergrated cutter with
hopper

Interfaces
Standard: Serial and USB
Optional: Ethernet, Bluetooth & Wi-Fi

Protocols
Standard: FGL
Drivers: Windows, Mac and Linux

Approvals
UL / FCC / CE / CCC

* Print speed may be affected at
extreme tempuratures

Power Requirements
100-240 VAC, 50/60 Hz, 80W max
24 V DC, 100W max

Environmental
* **Operating Temperature:** -20 to 60ºC
Relative Humidity: 10% to 90%
Storage Temperature: -40 to 70ºC
above specs without condensation

Bar Codes
Most 1D and 2D codes including PDF417,
DataMatrix, QR, Aztec

Full speed printing of picket fence and
ladder bar codes

Fonts
Resident fonts: 16 bitmapped fonts
(including Cyrillic and German characters)
and Asian character sets (optional)
Downloadable fonts: HP Soft fonts /
TrueType fonts
Downloadable RAM: up to 27MB
Downloadable Flash: up to 28MB (optional)

Graphics
FGL format, PCX format (1bit b/w), BMP
format (1bit b/w)

Web Interface (ethernet only)
Real-time status monitor
Email notification

Projected Life
Cutter: 1 million cuts
Print Head: 150 km of paper
or 100 million dot activations
Bonus: Free print head replacements
when exclusively using Boca paper

Warranty
Printer: 1 year, parts and labor
Print head: 90 days

Patents: BOCA has a patented head
protection system that prevents premature
head failure